



BEAMS STANDARD "I"



DEPTH	WEB THICKNESS	FLANGE WIDTH	FLANGE THICKNESS	AREA SQ. IN.
S3x5.7	0.170	2.330	0.260	1.67
7.5	0.349	2.509	0.260	2.21
S4x7.7	0.193	2.663	0.293	2.26
9.5	0.326	2.796	0.293	2.79
S5x10.0	0.214	3.004	0.326	2.94
14.75	0.494	3.284	0.326	4.34
S6x12.5	0.232	3.332	0.359	3.67
17.25	0.465	3.565	0.359	5.07
S7x15.3	0.252	3.662	0.392	4.50
20.0	0.450	3.860	0.392	5.88
S8x18.4	0.271	4.001	0.425	5.41
23.0	0.441	4.171	0.425	6.77
S10x25.4	0.311	4.661	0.491	7.46
35.0	0.594	4.944	0.491	10.30
S12x31.8	0.350	5.000	0.544	9.35
35.0	0.428	5.078	0.544	10.30
40.8	0.472	5.252	0.659	12.00
50.0	0.687	5.477	0.659	14.70
S15x42.9	0.411	5.501	0.622	12.60
50.0	0.550	5.640	0.622	14.70
S18x54.7	0.461	6.001	0.691	16.10
70.0	0.711	6.251	0.691	20.60
S20x66.0	0.505	6.255	0.795	19.40
26.0	0.660	7.060	0.920	25.00